

Transmitter EC28 i

for toxic gases, oxygen and hydrogen



- ATEX certified Ex II 1 G Ex ia IIC T4
- One-man calibration at transmitter via remote control
- Plug-in Smart Sensor
- Sensor replacement without opening housing
- Intrinsically safe

Worldwide Supplier Of Gas Detection Solutions



Transmitter EC28 i

Superior technology

Wherever gas hazards are to be expected, the transmitter EC28 i and GfG's proven control systems are the right choice for reliable surveillance. The ATEX-certified design provides the highest safety even in hazardous areas. LEDs indicate operation (green) or fault (red).

The transmitter EC28 i is certified intrinsically safe to give the highest possible level of safety.

Smart sensors

Smart Sensor technology allows the user to install the transmitter or to replace a sensor within a few seconds – just plug the sensor into the transmitter. Adjustments are done directly at the transmitter via touch keys or with the remote control (one man calibration).

Remote Control RC2

Ammonia and hydrogen are lighter than air. With the transmitter installed close to the ceiling you can provide permanently connected cable with plugs for the remote control, which allows the user to do all adjustments without having to climb a ladder. One remote control can be used for several transmitters. The remote control always shows the same reading as

the transmitter. The remote control simplifies inspection, service and calibration considerably. In addition to this, the remote control reads the current gas concentration and can be used as an external display.

Reliable detection and minimized cost of ownership

The sensor and integrated temperature compensation provide highest measurement accuracy. Low maintenance requirements and long sensor life reduce your cost of ownership.

Versions

EC28 basic unit without display.

EC28 D with display of actual gas concentration.

EC28 DA with display, bright alarm LEDs and integrated buzzer. No need for an expensive Ex-proof buzzer means less wiring costs.

EC28 DAR includes a relay for additional external alarm devices.

EC28 B with BUS-interface.

EC28 DB with BUS-interface and display of actual gas concentration.

EC28 DAB with BUS-interface and display of actual gas concentration and with bright alarm LED and integrated buzzer. No need for an expensive Ex-proof buzzer means less wiring costs.

EC28 Di intrinsically safe and with display of actual gas concentration.



RC2 with EC28 DA

In combination with GfG's flexible controllers the transmitter EC28 provides many possibilities for reliable and cost effective monitoring toxic gases.

Advantages at a glance

- ATEX-approval
- Plug-in smart sensor for easy sensor replacement
- Long sensor life
- Low service requirement
- Calibration without opening housing
- Intrinsically safety

Transmitter EC28 i Technical Data

Detection principle:

Electrochemical sensor

Weight:

800 g

ATEX labelling:

ⒺII 1 G Ex ia IIC T4
C_E0158

Ambient temperature:

-20°C .. +50°C

Dimensions:

100x193x55 mm (WxHxD)

Output signal:

4 – 20 mA

Casing protection:

IP64

Transmitter cable:

Shielded cable
2/3/6 x 0.75mm²
M 16 x 1,5

Supply voltage:

15 – 30 V DC

Display:

LED for operation / fault



Gases and Detection Ranges (ppm)

All detection ranges are scalable - except HF and O₃ (0 - 1 ppm)

Ammonia NH ₃	Chlorine Cl ₂	Chlorine dioxide ClO ₂	Hydrogen chloride HCl	Hydro cyanide HCN	Ethylene oxide C ₂ H ₄ O	Hydrogen fluoride HF	Carbon monoxide CO	
0 - 200 0 - 500 0 - 1000	0 - 50 0 - 250	0 - 2	0 - 30 0 - 200	0 - 50 0 - 200	0 - 100	0 - 10	0 - 500 0 - 2000	
Ozone O ₃	Phosgene COCl ₂	Oxygen O ₂	Sulphur dioxide SO ₂	Hydrogen sulphide H ₂ S	Silane SiH ₄	Nitrogen dioxide NO ₂	Nitrogen monoxide NO	Hydrogen H ₂
0 - 1 0 - 5	0 - 2	0 - 30 Vol.-%	0 - 50 0 - 500	0 - 200 0 - 1000	0 - 50	0 - 50 0 - 200	0 - 300 0 - 1500	0 - 2000 0 - 1 Vol.-% 0 - 4 Vol.-%



GfG Headquarters

Klönnestrasse 99
44143 Dortmund • Germany
Phone: +49 / (0)231 - 564 000
info@gfg-mbh.com • www.gasmessung.de

GfG Europe

Great Dunmow
Essex CM6 1XG • United Kingdom
Phone: +44 / (0)1371 - 874 447 • Fax: +44 / (0)1371 - 879 904
info@gfgeurope.com • www.gfgeurope.com